

B-Smart

Basic - Flow rate Indicator / Totalizer with pulse and analog output



Features

- Compact design.
- Displays instantaneous flow rate, total and accumulated total.
- Durable IP65 (Type4) field, wall or meter mount enclosure.
- One 20mm (0.79") and two 16mm(0.63") knock-out hole cable entries.
- "Know one, know them all" configuration structure.
- Easy reading and programming with clear alphanumeric display.
- Clear 12mm(0.5") numeric digits and 7mm(0.3") alphanumeric digits.
- Bright LED backlight.
- Auto backup of settings and running totals.
- Lithium AA battery and 10 - 30V DC power supply.
- Sensor supply: 8.2V DC.

Product description

The B-Smart flow transmitter is the most advanced model in our B-Series, complete with pulse and analog output signals. The display shows flow rate, total and accumulated total. On-screen engineering units are easily configured from a comprehensive selection.

Advantages

- The B-Series is our most cost effective display but with all the benefits you may expect from a Fluidwell product: It's durable, reliable and very easy to operate. Basic with a capital B!
- Familiar easy operation with the Fluidwell "Know one, know them all" configuration structure, saving time, cost and aggravation.

Applications

- Basic flow measurement where re-transmission of the flow rate and/or totalizer functions is required.
- The B-series offers you an economical solution for common industrial applications. Nothing

more, nothing less.

Product specifications

Signal Inputs

Flowmeter Inputs

- Basic types of flowmeter signals: Namur, Reed-switch, NPN, PNP and Sine wave (coil).

Supply

Power Supply

- A single 3,6V lithium AA battery.
- 10 – 30V DC.

Sensor Supply

- 8.2V DC.

Signal Outputs

Pulse outputs

- Function: Scaled pulse output according to accumulated total (e.g. a pulse every 3.25 gallons).
Frequency: User definable 100Hz (5msec) or 5Hz (100msec).
- Type: One passive transistor output (NPN) - not isolated.

Alarm outputs

- None.

Analog outputs

- Function: Re-transmitting the flow rate - the output can be scaled to any range (e.g. 200 L/min to 1200 L/min).
- Type: One loop powered 4 – 20mA output.

Control outputs

- None.

Hazardous Area

Intrinsically Safe

- For Intrinsically Safe applications we recommend the F-Series.

Explosion Proof

- For Explosion Proof applications we recommend the E-Series.

Communication

- Modbus communication available on F1-Series products.
- HART communication is available with the F018 & E018 Flow rate Monitor / Totalizers.



sales@fluidwell.com | T. +31 (0) 413 - 434 786

We're happy to answer any questions about our products and services.
Just send us an email or give us a call.