

F013 Intrinsically Safe - Flow rate Monitor / Totalizer

with one high / low alarm output



Features

- Flow rate monitoring: two alarm values can be set: low and high flow rate alarm.
- Alarm values can be changed by the operator or they can be password protected.
- One alarm output for high, low or both combined flow rate alarms.
- Displays total and flow rate simultaneously.
- Large digit selection for flow rate or total.
- Flow rate: seven 17mm (0.67") or 8mm (0.31") digits.
- Total - resettable: seven 17mm (0.67") digits.
- Accumulated total - not resettable: eleven 8mm (0.31") digits.
- Separate engineering units for flow rate and total.
- Red flashing LED backlight in case of a flow rate alarm; intensity adjustable.
- Displays clear alarm messages.
- Intrinsically safe according ATEX, IECEx, FM and CSA C-US.
- GRP, Aluminum or high grade stainless steel enclosure.
- Auto backup of settings and running totals in EEPROM memory.
- Easy configuration with clear alphanumeric display.
- Ambient temperature: -40°C to +80°C (-40°F to 176°F).
- Various [accessories](#) are available for this product.

Product description

The F013 is a versatile flow rate indicator and totalizer with continuous flow rate monitoring feature. It offers the ability to set one low flow rate and one high flow rate alarm value. If desired, an alarm ignore function can be set up to allow for an incorrect flow rate for a certain period of time. The display shows flow rate, total, accumulated total, alarm values and alarm messages. On-screen engineering units are easily configured from a comprehensive selection.

Advantages

- Robust aluminum or stainless steel 316L field enclosure (IP66, IP67 / NEMA Type4X) . It is so rugged, a truck can even stand on it!
- Intrinsically Safe available - ATEX, IECEx, FM and CSA approval for gas and dust applications.

- Familiar easy operation with the Fluidwell "Know one, know them all" configuration structure, saving time, cost and aggravation.
- Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors.

Applications

- Flow measurement where continuous flow rate monitoring is important without signal re-transmission.
- The F-Series is your first and best choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, sandy deserts, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).

Product specifications

Signal Inputs

Flowmeter Inputs

- Pulse type inputs:
Reed-switch, NAMUR, NPN/PNP pulse, Sine wave (coil), active pulse signal.
- (0)4 - 20mA.

Supply

Power Supply

- Long life Lithium battery.
- 4 - 20mA, input Loop-powered.
- 8 - 24V AC/DC.
- 115 - 230V AC.
- Basic: 8 - 30V DC.

Sensor Supply

- 3.2, 8.2, 12, 24V DC.

Signal Outputs

Pulse outputs

- None.

Alarm outputs

- Function: Configurable alarm output for high, low or both combined flow rate alarms.
- Type: One passive NPN transistor, active PNP transistor or isolated electro-mechanical relay.

Analog outputs

- None.

Hazardous Area

Intrinsically Safe

- ATEX:
Gas: II 1 G Ex ia IIC T4 Ga
Dust: II 1 D Ex ia IIIC T100°C Da
- IECEX:
Gas: Ex ia IIC T4 Ga
Dust: Ex ia IIIC T100°C Da
- CSA:
I.S. Class I/II/III, Div 1, Grp A...G, T4
Class I, Zone 0, AEx ia IIC T4
- FM:
I.S. Class I/II/III, Div 1, Grp A...G, T4
Class I, Zone 0, AEx ia IIC T4

Explosion Proof

- ATEX:
Gas: II 2 G / Ex d IIB T5 Gb
Dust: II 2 D / Ex t IIIB T100°C Db

Communication

- Modbus communication available on F1-Series products.

- HART communication is available with the F018 & E018 Flow rate Monitor / Totalizers.



sales@fluidwell.com | T. +31 (0) 413 - 434 786

We're happy to answer any questions about our products and services.
Just send us an email or give us a call.