

F093

Intrinsically Safe - Tachometer Monitor

displays engine speed and running hours with alarm output



Features

- Displays engine speed and running hours simultaneously.
- Various alarm values can be entered: low / high engine speed alarm and total running hours alarm.
- Large 17mm (0.67") digits for engine speed or running hours.
- Red flashing LED backlight in case of an alarm; intensity adjustable.
- Intrinsically safe according ATEX, IECEx, FM and CSA C-US.
- GRP, Aluminum or high grade stainless steel enclosure.
- Auto backup of settings in EEPROM memory.
- Easy configuration with clear alphanumeric display.
- Ambient temperature: -40°C to +80°C (-40°F to 176°F).
- Various accessories are available for this product.

Product description

The F093 is a local indicator to monitor the tachometer engine speed with running hours simultaneously. The running hours can be reset to zero by pressing the CLEAR button twice. The eleven digit accumulated running hours however can not be reset to zero.

Advantages

- Robust aluminum or stainless steel 316L field enclosure (IP66, IP67 / NEMA Type4X) . It is so rugged, a truck can even stand on it!
- Intrinsically Safe available - ATEX, IECEx, FM and CSA approval for gas and dust applications.
- Familiar easy operation with the Fluidwell "Know one, know them all" configuration structure, saving time, cost and aggravation.
- Very diverse mounting possibilities: walls, pipes, panels or directly onto outdoor sensors.

Applications

- Tachometer applications where monitoring of the engine speed and running hours is important and both need to be displayed and registered.
- The F-Series is your first and best choice for field mount indicators in safe and hazardous area applications. Especially in harsh weather conditions like rain, snow, sandy deserts, salty atmospheres and temperatures between -40°C up to +80°C (-40°F up to 176°F).

Product specifications

Signal Inputs

General Purpose Inputs

- Pulse inputs from tachometers:
Reed-switch, NAMUR, NPN/PNP pulse, Sine wave (coil), active pulse signal.

Supply

Power Supply

- Long life Lithium battery.
- 8 - 24V AC/DC.
- 115 - 230V AC.
- Basic: 8 - 30V DC.

Sensor Supply

- 8.2, 12, 24V DC.

Signal Outputs

Alarm outputs

- Function: Configurable alarm output to transmit the engine speed alarm or total running hours alarm
- Type: One passive NPN transistor, active PNP transistor or isolated electro-mechanical relay.

Analog outputs

- None.

Hazardous Area

Intrinsically Safe

- ATEX:
Gas: II 1 G Ex ia IIC T4 Ga
Dust: II 1 D Ex ia IIIC T100°C Da
- IECEx:
Gas: Ex ia IIC T4 Ga
Dust: Ex ia IIIC T100°C Da
- CSA:
I.S. Class I/II/III, Div 1, Grp A...G, T4
Class I, Zone 0, AEx ia IIC T4
- FM:
I.S. Class I/II/III, Div 1, Grp A...G, T4
Class I, Zone 0, AEx ia IIC T4

Explosion Proof

- ATEX:
Gas: II 2 G / Ex d IIB T5 Gb
Dust: II 2 D / Ex t IIIB T100°C Db

Communication

- Modbus communication available on F1-Series products.
- HART communication is available with the F018 & E018 Flow rate Monitor / Totalizers.



sales@fluidwell.com | T. +31 (0) 413 - 434 786

We're happy to answer any questions about our products and services.
Just send us an email or give us a call.